

# 200 - 300 SL

## HYDROMANN

### **Salt and grit spreader 200 - 300 SL**

A self-loading spreader for compact tractors. To satisfy customer demands, this hydraulic spreader has a large accessory program making it ideal for many work applications. The simple durable construction ensures low maintenance costs. This machine works under all road and weather conditions, and can cope with the harshest of salt-spreading conditions. Furthermore, the flow regulator and the double-acting top link are standard equipment. The spreader can also be mounted on small front loaders. For minimum salt spreading, special salt cams can be mounted to achieve a salt dosage as low as 10 gr. m<sup>2</sup>.



### **Salt and grit spreader:**

- > Roller with replaceable cams
- > Agitator
- > Adjustable spring base
- > 3-point hitch cat. 0 + 1
- > Emptying function
- > Flow regulator and double-acting top link



**Hydromann a/s, Nylandsvej 36, DK-6940 Lem St.**  
**Tlf.: +45 97 34 12 33 - Fax: +45 97 34 19 09.**  
**Sales@hydromann.dk - www.hydromann.dk**

## Technical details: (200 - 300 SL)

<b>Total width</b>	<b>1160 - 1420 mm</b>
<b>Spread width</b>	<b>1000 - 1260 mm</b>
<b>Capacity</b>	<b>200 - 250 litre</b>
<b>Spread distance: Salt at 20 gr./m<sup>2</sup></b>	<b>11 km</b>
<b>Spread distance: Sand at 200 gr./m<sup>2</sup> Weight:</b>	<b>2 km 178 - 202 kg</b>
<b>Oil requirement</b>	<b>20 litre. / 125 bar</b>
<b>Surface treatment</b>	<b>Zinc + Primer + 2 component top coat</b>

### Accessories:


- Hopper extension
- Various cams
- Flow regulator
- Drive-dependent control
- Electrical change valve
- Tarpaulin
- Lighting



Adjustment of spring base



Agitator over roller



3-point hitch with hydraulic top link and flow regulator

# HYDROMANN

Dealer:

Hydromann a/s  
Nylandsvej 36  
DK-6940 Lem St.  
Tlf.: +45 97 34 12 33  
Fax: +45 97 34 19 09.  
[www.hydromann.dk](http://www.hydromann.dk)