

1500 S - 2000 S

HYDROMANN

Salt and grit spreader 1500 S - 2000 S

This series of salt and grit hydraulic spreaders can be used for all types of tractor with hydraulic outlets. The simple construction with strong durable parts, keep maintenance costs low. The machines work under all road and weather conditions and are, as standard, provided with a flow regulator and an emptying function. You can spread sand, salt, gravel or oil absorbents.



Salt and grit spreader:

- > Roller with replaceable cams
- > Agitator
- > Adjustable spring base with emptying function
- > 3-point hitch cat. 2
- > Flow regulator
- > Grating

Hydromann a/s, Nylandsvej 36, DK-6940 Lem St.
Tlf.: +45 97 34 12 33 - Fax: +45 97 34 19 09.
Sales@hydromann.dk - www.hydromann.dk

Technical details (1500 S - 2000 S)

Total width	1650 - 2150 mm
Spread width	1500 - 2000 mm
Capacity	600 - 800 litre
Spread distance Salt at 20 gr./m²	20 km
Spread distance Sand at 200 gr./m²	5 km
Weight	280 - 350 kg
Oil requirements	35 litre / 120 bar
Surface treatment	Zinc + Primer + 2 component top coat

Accessories


- Drive-dependent control
- Electrical change valve
- Lighting
- Roller shield



Adjustment of spring
base with emptying
function



3-point hitch and hydraulic flow
regulator



Grating

HYDROMANN

Dealer:

Hydromann a/s
Nylandsvej 36
DK-6940 Lem St.
Tlf.: +45 97 34 12 33
Fax: +45 97 34 19 09.
www.hydromann.dk