

TSL 16

HYDROMANN



The showing models can be with extra equipment

Salt and grit disc-spreader TSL 16

- > Spread width 2-8 meter
- > Adjustable spread symmetry
- > Hydraulically powered
- > Changeable hitch A-frame/3-point/HMV/SMS
- > Substantial guard around disc when loading
- > Strong construction with 6 mm steel plates
- > Quick mounting of supporting leg

Hydromann a/s, Nylandsvej 36, DK-6940 Lem St.
Tlf.: +45 97 34 12 33 - Fax: +45 97 34 19 09.
Sales@hydromann.dk - www.hydromann.dk

Technical details (TSL 16)

Width	230 cm
Height	145 cm
Length	135 cm
Weight	675 kg
Capacity	1600 litre
Oil requirement	25 l/min.
Required hydr. output	2-3 stk. double-acting
Disc diameter	410 mm
Surface treatment	Zinc + Primer + 2 comp. top coat

Accessories:

- Drive-dependent control
- Tarpaulin
- Lighting
- A-frame
- HMV/SMS




Snail and mixer. The snail has rising turns for an even emptying of the container to the center.



Electrical controlling of the spread and strewing quantity from the leader house.



Höhenverstellbare
one Supporting legs



Exchangeable suspension



The material supply is steered hydraulically via a mobile slide-gate valve.

HYDROMANN

Hydromann a/s
Nylandsvej 36
DK-6940 Lem St.
Tlf.: +45 97 34 12 33
Fax: +45 97 34 19 09.
www.hydromann.dk